



॥ राष्ट्रदेवो भवः ॥



Since 1994



## SSP SERIES



Bath Shower



Gardening



Domestic



Water Supply



Industrial



Mfg. by : **Falcon Pumps Pvt. Ltd.**

Chale Pragati Ki Aur®

✉ [sales@falconpumps.in](mailto:sales@falconpumps.in) | ✉ [info@falconpumps.in](mailto:info@falconpumps.in) | ☎ 1800 123 0000

## ■ SSP SERIES

Falcon regenerative monoset pumpsets are powered by a totally enclosed fan cooled AC induction two pole motor. Motor stator is made of low watt loss silicon steel laminations assembled under pressure and rigidly locked in the frame. The windings are of high-grade enameled copper wire offer excellent resistance and are varnish impregnated. Construction of motor frame and usage of quality materials result in high performance and low temperature rise thereby increasing the life cycle of the motor.

## ■ SALIENT FEATURES

- High operating efficiency resulting in lower power consumption.
- Good suction lift characteristics.
- Specially designed for wide voltage operation.
- Dynamically balanced rotating parts including rotor and impeller ensures minimum vibration and longer life.
- Back pull-out design for easy servicing and repair.
- Double shielded ball bearings, so no need of external lubrication.
- All Model fitted to Mechanical seal.



## ■ SPECIFICATION

- Power Range	: 0.37 Kw - 0.75 Kw (0.5 HP - 1.0 HP)
- Version	: Single Phase, 220-240V, 50Hz AC Supply
- Speed	: 1440 RPM
- Maximum Total Head	: 18 Mtr.
- Maximum Flow Rate	: 4200 LPH
- Maximum Suction Lift	: 8 Mtr.
- Degree of Protection	: IP 44
- Class of Insulation	: B
- Maximum Ambient Tem.	: 40°C
- Sealing	: Mechanical Seal
- Type of Duty	: S1 (Continuous)
- Direction of Rotation	: Single Phase, Clockwise from driving end
- Nominal Pumpset Size (Suction X Delivery)	: 25mm X 25mm



**Double ZZ  
SKF Bearing**



**CRNGO  
Progressive Cutting  
Stamping Stack**



**High Tech  
Mechanical Seal**




## ■ CHARACTERISTICS OF CLEAR COLD WATER

- Maximum liquid temperature : 33°C max
- Permissible amount of sand : 25 g/m<sup>3</sup>
- Allowable solids : 3000 ppm (max.)
- Chloride ion density : 500 ppm (max.)
- Turbidity : 50 ppm silica scale (max.)
- Hardness (Drinking Water) : 300 ppm (max.)
- Specific gravity : 1.004 (max.)
- Viscosity :  $1.75 \times 10^6$  m<sup>2</sup>/sec (max.)
- Ph Value : 6.5 to 8.5



**Aluminum  
Die Cast Rotor Stack**



**Centrifugal  
Switch**





## ■ MATERIAL OF CONSTRUCTION - MOTOR

<u>Part Name</u>	<u>Material</u>
Mechanical Seal	: Carbon & Ceramic
Motor Shaft	: SS-410
Motor Body	: FG-250
Bearing	: SKF
End Cover	: FG-250
Bracket	: FG-250
Flange	: FG-250
Casing	: FG-250
Impeller	: Brass
Cooling Fan	: Plastic

