

Domestic Single Stage Horizontal Openwell

50 Hz - 230 Volt in Single Phase & 415 Volt. in Three Phase, 2800 RPM with CED Coated Casting Parts.

Horizontal
Openwell

C.I. Openwell - CI-DSH Series

C.I. Body, C.I. Impellers with Copper Rotor.

Sr. No.	Model	H.P.	Suction x Delivery in Inch	Del. Schedule	Total Head In Metre & Discharge in LPM											Over all Effi. % as per IS 14220/18	Falcon Max. Overall Effi. in%		More Result Compare to IS	Achieved Star as per BEE Calcu.	
					6	8	10	15	16	18	20	22	24	26	28		30	SP			TP
					1	CI DSH-0518	0.5	1.0 x 1.0	1	168	160	150	120	105	90		60	-			-
2	CI DSH-130	1.0	1.25x1.25	1	225	210	200	180	175	165	160	150	135	120	100	80	17.50	29.50	30.00	71%	8
3	CI DSH-01528	1.5	2.0 x 2.0	2	305	290	280	260	240	225	210	180	165	135	95	-	20.52	33.00	34.00	66%	7
4	CI DSH-228	2.0	2.0 x 2.0	2	385	375	360	330	300	280	260	240	210	180	150	100	27.06	36.00	39.00	44%	5
5	CI DSH-318	3.0	2.5 x 2.5	2	750	710	680	550	525	480	-	-	-	-	-	-	36.28	45.00	48.00	32%	4
6	CI DSH-324	3.0	2.5 x 2.5	2	660	645	620	570	550	520	480	440	400	360	-	-	36.57	43.00	45.00	23%	3
7	CI DSH-330	3.0	2.0 x 2.0	2	545	530	510	490	480	455	430	400	370	330	280	230	31.05	43.00	44.00	42%	5

NOTE : 0.5 H.P. Model is Single Phase Only.

NOTE : Performance May Vary Depending Upon Voltage, Frequency and Field Conditions.

Chale Pragati Ki Aur®

