

Domestic Single Stage Horizontal Openwell

50 Hz - 230 Volt in Single Phase & 415 Volt. in Three Phase, 2800 RPM with CED Coated Casting Parts.

Horizontal
Openwell

S.S. Openwell - DSH Series

S.S. Body, C.I. Impellers with EC grade Copper Rotor / Aluminium Rotor covered with S.S.Cap

Sr. No.	Model	H.P.	Suction x Delivery in Inch	Del. Schedule		Total Head In Metre & Discharge in LPM											Over all Effi. % as per IS 14220/18	Falcon Max. Overall Effi. in%		More Result Compare to IS	Achieved Star as per BEE Calcul.	
				Alu.	Cop.	6	8	10	15	16	18	20	22	24	26	28		30	SP			TP
1	DSH-0518	0.5	1.0 x 1.0	1	-	168	160	150	120	105	90	60	-	-	-	-	-	15.20	27.00	-	-	-
2	DSH-130	1.0	1.25 x 1.0	1	-	225	210	200	180	175	165	160	150	135	120	100	80	17.50	29.50	30.00	71%	8
3	DSH-01528	1.5	2.0 x 2.0	2	-	305	290	280	260	240	225	210	180	165	135	95	-	20.52	33.00	34.00	66%	7
4	DSH-228	2.0	2.0 x 2.0	2	2	385	375	360	330	300	280	260	240	210	180	150	100	27.06	36.00	39.00	44%	5
5	DSH-324	3.0	2.5 x 2.5	2	2	660	645	620	570	550	520	480	440	400	360	-	-	36.57	43.00	45.00	23%	3
6	DSH-330	3.0	2.0 x 2.0	2	2	545	530	510	490	480	455	430	400	370	330	280	230	31.05	43.00	44.00	42%	5

NOTE : (1) 0.5 H.P. Model is Single Phase Only, (2) 0.5 H.P. & 1.0 H.P. Price are With Panel

NOTE : Performance May Vary Depending Upon Voltage, Frequency and Field Conditions.

Chale Pragati Ki Aur®

